



## Rack PDU, Basic, ZeroU, 16A, 230V, 20 x C13 & 4x C19 Outputs, IEC-309 16A Input

APC Basic Rack PDU , Input: 230V , Input Connections: IEC 309 16A 2P+E , Cord Length: 3 feet ( 0.91 meters ) , Output: 230V , Output Connections: IEC 320 C13, IEC 320 C19


Part Number : **AP7551**

### The most mounting options in the market.

APC offers a wide variety of Basic Rack Power Distribution Units (PDUs), which allow users to distribute power outlets to rack-mount equipment. Horizontal and vertical units are available as well as a variety of power inputs and outputs to fit most power environments. APC now offers Basic Rack PDUs that mount vertically, without tools in the rear channel of a NetShelter VX.

### Technical Specifications

#### Output

Nominal output voltage	230V
Maximum Total Current Draw per Phase	16 A
Output Connections	(20) IEC 320 C13  (4) IEC 320 C19

#### Input

Nominal input voltage	230V
Input frequency	50/60 Hz
Input Connection Type	IEC 309 16A 2P+E
Cord Length	10 feet
Maximum Input Current per phase	16 A
Load Capacity	3680 VA

### Physical

Net weight	10.70 lbs. ( 4.86 kg )
Maximum height	63.75 inches ( 1619 mm )
Maximum width	2.20 inches ( 56 mm )
Maximum depth	1.73 inches ( 44 mm )
Shipping Weight	12.70 lbs. ( 5.77 kg )
Shipping Height	84.00 inches ( 2134 mm )
Shipping Width	6.00 inches ( 152 mm )
Shipping Depth	5.00 inches ( 127 mm )
Color	Black

### Conformance

Approvals	CE , EN 60950 , VDE
Standard warranty	2 years repair or replace

### Environmental

Operating Environment	0 - 45 °C ( 32 - 113 °F )
Operating Relative Humidity	5 - 95 %
Operating Elevation	0-10000 feet ( -3000 meters)
Storage Temperature	-25 - 65 °C ( -13 - 149 °F )
Storage Relative Humidity	5 - 95 %
Storage Elevation	0-50000 feet ( 0-15000 meters )